



1000 Western Drive  
 Brunswick, OH 44212  
 PHONE: 330/225-3200  
 FAX: 330/225-1499  
 www.columbiachemical.com

# NiCOL™ ANTIPIIT 1

ADDITIVE FOR NICKEL PLATING BATHS  
 TECHNICAL DATA  
 3-17-15

## NiCOL ANTIPIIT 1 ADDITIVE FOR NICKEL PLATING BATHS

- NiCOL ANTIPIIT 1 is an additive to eliminate pitting from organic contamination
- NiCOL ANTIPIIT 1 helps to disperse or break up organics to eliminate pitting
- NiCOL ANTIPIIT 1 can be used either as a one- time addition or through maintenance additions

### *Solution Composition*

	<u>Range</u>	<u>Optimum</u>
NiCOL ANTIPIIT 1	0.01 - 0.1%/vol (0.1 - 1.0 ml/Liter)	0.025%/vol

**NiCOL ANTIPIIT 1**- contains dispersing agents that help remove pitting in air agitated nickel-plating baths. Under ideal conditions little or none is required, however small additions or maintenance additions of the NiCOL ANTIPIIT 1 helps to insure a pit or pore free deposit. NiCOL ANTIPIIT 1 is removed by carbon: either batch treatment or carbon packed filter.

## **HANDLING & STORAGE**

NiCOL additives can produce temporary irritation when they come into contact with the skin. Therefore, care should be taken to prevent accidental eye and skin contact. Rubber gloves, a rubber apron, and protective goggles should be worn when handling NiCOL additives. In case of contact, immediately flush with copious amounts of water and scrub well with soap and water. NiCOL additives are stable on standing and have a shelf life in excess of two years.

**FREEZABILITY:** As with most chemical products, it is preferable that freezing be avoided. However, if freezing should occur during transportation or storage, directions for handling the products covered in this technical data sheet are as follows:

If NiCOL ANTIPIT 1 freezes, simply allow the container to completely thaw and bring to room temperature of 70° - 75°F/ 21° - 24°C. Thoroughly mix to bring back to original condition.

## **NON-WARRANTY**

The data in this bulletin is believed by Columbia Chemical Corp. to be accurate, true, and complete. Since, however final methods of use of this product are in the hands of the end-user and beyond our control, we cannot guarantee that the end-user will obtain the results described in this bulletin, nor can we assume any responsibility of the use of this product by the end-user in any process which may infringe the patents of third parties.