

SECTION 1: COMPANY AND MIXTURE IDENTIFICATION

1.1 Product Name: Zinc-Chro-PELLENT

1.2 Product Type and Use: Metal Finishing Additive

1.3 Manufacturer:

Columbia Chemical Corp.
1000 Western Drive
Brunswick, OH, 44212
330-225-3200
eh&s@columbiachemical.com

Only Representative:

Intertek France
Campus Industrial Grand
Chalon Route de Demigny
Chalon Sur Saone
France, 71102
T: +33 (0) 385 99 1280

1.4 Emergency Telephone Numbers

CHEMTEL
US & CANADA 800-255-3924
INTERNATIONAL 01-813-248-0585

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the mixture according to GHS (EC 1272 -2008)

Skin Corr. 1A, H314
Eye Dam. 1, H318

2.2 GHS Pictograms and H/P Statements



Signal Word: **DANGER**

Hazard and Precautionary Statements:

H314A: Causes severe skin burns and eye damage.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P310: Immediately call a POISON CENTER or doctor/physician.

P501: Dispose of contents/container in accordance with all local/regional/national/international regulations.

H318: Causes serious eye damage

P264: Wash thoroughly after handling.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P363: Wash contaminated clothing before reuse.

2.3 Additional Information:

NONE

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Name	Product Identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
SILICIC ACID, SODIUM SALT	CAS no. 1344-09-8 EC no. 215-687-4 Reach no. JCSL no. 1-508	<60%	Skin Irrit. 2, H315 Eye Irrit. 2, H319
SILICONE RESIN SOLUTION	CAS no. T.S. EC no. 250-807-9 Reach no. Low volume exempt	< 15%	Skin Corr. 1A, H314 Eye Dam. 1, H318
ALIPHATIC AMINE	CAS no. T.S. EC no. 205-483-3 Reach no. Low volume exemption JCSL no. 2-301	< 3 %	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Corr. 1B, H314
ORGANIC SOLVENT	CAS no. T.S. EC no. 203-905-0 Reach no. Low volume exemption.	< 2%	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures**

Eye Contact:	Immediately flush eyes with flowing water for at least TWENTY (20) minutes. Call emergency medical services.
Skin Contact:	Flush exposed area with running water for at least TWENTY (20) minutes. Remove and isolate contaminated clothing. Get medical attention.
Inhalation:	Move exposed individual to fresh air. Give oxygen if breathing is difficult. Provide artificial respiration using a mask equipped with a one-way valve if victim is not breathing. Call emergency medical services.
Ingestion:	Provide large quantities of water if victim is conscious and call emergency medical services immediately. Never give anything by mouth to an unconscious person.

4.2 Important symptoms and effect acute and delayed

Symptoms/Injuries:	May cause eye irritation, burns or blindness.
Inhalation:	Inhalation of mist may cause irritation of the respiratory system.
Skin contact:	May cause severe burns. Symptoms might include pain, redness, and tissue damage.
Eye contact:	May cause serious damage to the eyes.
Ingestion:	May cause severe irritation of the digestive tract, nausea, vomiting, or diarrhea.

4.3 Indication of any immediate medical attention and special treatment needed

Seek immediate medical attention if splashed in eyes or if there is a difficulty in breathing while using this product.

SECTION 5: FIRE FIGHTING MEASURES**5.1 Extinguishing media**

Dry chemical powder. Water spray. Carbon dioxide (CO₂)

5.2 Special Hazards from the mixture

Mixture itself does not burn but may decompose upon heating to produce fumes. Cool plastic drum, pail or tote containers which may swell or rupture upon heating.

5.3 Advice for firefighters

Protection from firefighting:	Use self-contained breathing apparatus and chemically protective clothing. For further information refer to section 8, Exposure-controls/personal protection.
Other Information:	Avoid eye and skin contact. HMIS: 2-0-0-D

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures****6.1.1 Non-emergency personnel**

Ensure adequate ventilation, Use personal protective equipment.

6.1.2 Emergency responders

Ensure adequate ventilation, Use personal protective equipment.

6.2 Environmental precautions

Avoid discharge into soil, water or air.

6.3 Containment and clean up

Methods for cleaning up:	Contain spills, cover with absorbent, carefully sweep up material and transfer to a suitable container for disposal.
Other information:	Comply with local regulations for disposal.

6.4 Reference to other sections

Refer to section 8.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling**

Avoid contact with skin, eye and clothing. Avoid breathing dust, mist or spray. Refer to section 8 for exposure controls.

7.2 Storage and Incompatibles

Storage Condition(s):	Shelf life is two (2) years from date of manufacture.
-----------------------	---

Store tightly closed in a dry, cool and well-ventilated place.

Incompatible materials:

Product may react with strong acidic and strong basic solutions.

Storage area:

Floors should be impenetrable, resistant to liquids and easy to clean. Keep away from heat and direct sunlight. Do not store near oxidizing agents. Store in dry, cool, well-ventilated area.

7.3 Specific end use(s)

Metal Finishing

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 Control Parameters

ALIPHATIC AMINE (T.S.) USA	ACGIH - TEL	8 mg/m3
ORGANIC SOLVENT (T.S.) USA	ACGIH - TEL	24 mg/m3
SILICIC ACID, SODIUM SALT (1344-09-8)		
SILICONE RESIN SOLUTION (T.S.) USA	ACGIH - TEL	N/A

8.2 Exposure Controls

Exposure Controls:	Maintain employee exposures to levels below the applicable exposure limits.
Ventilation:	Use local or general exhaust to reduce airborne exposures.
Respiratory Protection:	To reduce exposure a NIOSH-approved respirator should be used.
Hand Protection:	Wear chemical resistant rubber gloves.
Eye Protection:	Wear chemical safety glasses and/or face shield.
Skin Protection:	Wear protective clothing as appropriate.
Other:	Launder contaminated clothing before reuse.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:	Clear to slightly hazy liquid	Flammability (solid,gas):	No data available
Odour:	No odor	Explosive Limits:	No data available
Odour Threshold:	No data available	Vapor Pressure:	No data available
pH:	11.0 - 13.0	Vapour Density:	No data available
Melting Point:	No data available	Relative Density:	No data available
Solidification Point:	No data available	Solubility:	Complete in water
Boiling Point:	No data available	Self Ignition Temperature:	No data available
Flash point:	No data available	Decomposition Temperature:	No data available
Evap rate rel to butylacetate:	No data available	Viscosity:	No data available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	Product is an acidic solution and may react vigorously with alkaline solutions.
10.2 Chemical Stability	Product is stable under normal conditions only. Product may not be stable under heat, moisture, pressure ventilation or exposure to incompatible or reactive materials.
10.3 Possibility of hazardous reactions	Product will not undergo polymerization.
10.4 Conditions to avoid	Keep away from heat. Keep out of direct sunlight.
10.5 Incompatible materials	Product may react with strong acidic and strong basic solutions.
10.6 Hazardous decomposition products	Oxides of nitrogen, chromium and sulfur.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Toxicological effects

Acute toxicity:	No known acute toxicity effects when used as directed.
Skin corrosion/irritation:	Causes severe skin burns and eye damage.
Respiratory or skin sensitization:	May cause skin or respiratory sensitization with susceptible persons.
Embryotoxic, Teratogenic, or Mutagenic:	None.
Carcinogenicity:	None.
Reproductive or Gonadotoxicity:	None.
Specific target organ toxicity (single exposure):	None.

CARCINOGENS :

IARC : NONE
NTP : NONE

OSHA : NONE
EU : NONE

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity Material may be harmful to aquatic life if enough is released into waterways.
12.2 Persistence & Degradability No persistence and biodegradability data available.
12.3 Bioaccumulative Potential No known bioaccumulative potential.
12.4 Mobility in Soil No known mobility in soils.
12.5 PBT and vPvB Assessment A PBT or vPvB assesment has NOT been completed for this product.
12.6 Other Adverse Effects No other adverse affects known.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**

Waste Disposal: Dispose of this material and its container to hazardous or special waste collection point. Disposal must be done according to official regulations. Do not empty into drain or the aquatic environment.
Ecology - waste materials: Dispose of all waste in accordance with federal, state, and local regulations.

SECTION 14: TRANSPORTATION INFORMATION**U.S. DOT (Land)****Department of Transportation**

Proper Shipping Name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
 (ETHANOLAMINE)
 Hazard Class: 8
 UN / NA Number: 3267
 Packing Group: III
 Labels Required: CLASS 8 CORROSIVE
 Marine Pollutant: NONE

I.A.T.A / I.C.A.O. (AIR)**International Air Transportation Authority / International Civil Air Organization**

Proper Shipping Name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
 (ETHANOLAMINE)
 Hazard Class: 8
 UN / NA Number: 3267
 Packing Group: III
 Labels Required: CLASS 8 CORROSIVE
 Marine Pollutant: NONE

I.M.D.G. (Sea)**International Maritime Organization**

Proper Shipping Name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
 (ETHANOLAMINE)
 Hazard Class: 8
 UN / NA Number: 3267
 Packing Group: III
 Labels Required: CLASS 8 CORROSIVE
 Marine Pollutant: NONE

ERG Info: GUIDE # 153
 Reportable Quantity: NONE
 Placard: AS REQUIRED

14.5 Environmental Hazards This mixture is considered environmentally hazardous according to the UN Model Regulations and is considered ;
 marine pollutant according to the IMDG Code.
14.6 Special Precautions No other special precautions are required for transport of this mixture.

SECTION 15: REGULATORY INFORMATION**15.1 Safety, Health and Environmental Regulations.**

Classification according to Directive 1999/548/EC
 C; R34

DPD Pictograms



Risk and Safety Phrases:

R34, R36//38, S26, S36/37, S45, S46

INGREDIENT	CAS NUMBER	CERCLA	SARA 313	SARA 302	REACH SVHC List	ROHS 2
------------	------------	--------	----------	----------	-----------------	--------

NATIONAL INVENTORIES:

AICS (Australia):	Status not determined	ECN (Taiwan):	Components listed
DSL (Canada):	Components listed	NDSL (Canada):	Not all components listed
ECL (Korea):	Components listed	NZIoC (New Zealand):	Components listed
EINECS (Europe):	Components listed	PICCS (Philippines):	Components listed
ENCS (Japan):	Components listed	SWISS (Switzerland):	Status not determined
IECSC (China):	Components listed	TSCA (USA):	Components listed

WHMIS: Components listed as CANADA WHMIS Class E/B3 - Corrosive Material/ Combustible Material.

15.2 Chemical Safety Assessment A Chemical Safety Assessment has not been carried out for this mixture by the supplier.

SECTION 16 : OTHER INFORMATION**16.1 Method of Evaluation**

Mixture hazard classification per UN GHS Purple Book, (EC) 1272/2008 Article 9(4), OSHA Haz-Com 2012.

16.3 Other Information

This information is provided in good faith from current, reliable sources and is believed to be correct. No warranty is expressed, implied, or given. The seller of this material assumes no responsibility for any damages resulting from contact with this material

16.4 Revision History

6/5/15; Rev. GHS format.
10/28/14: Rev. S2, 14 and 16.
12/12/12: New release.